

	FX 22	FX 26	FX 30	FX 34
POWER				
Battery Module Option (battery modules are removable and interchangeable)	30Ah Lithium (20Kg) 60Ah Lithium (40Kg)		30Ah Lithium (20Kg) 60Ah Lithium (40Kg) 105Ah Lithium (43Kg)	
Battery Charger	Delta Q			
Run Time Battery (dependent on set-up and conditions)	2.5 - 3.5 hrs (30Ah) 5 - 7 hrs (60Ah) 8 - 10 hrs (105Ah)		2.5 - 3.5 hrs (30Ah) 5 - 7 hrs (60Ah) 8 - 10 hrs (105Ah)	
Approx. recharge time	4 hrs (30Ah) 6 hrs (60Ah)		4 hrs (30Ah) 6 hrs (60Ah) 8 hrs (105Ah)	
TRACTION AND DRIVE				
System Voltage	48V			
Traction Drive	1 kw Continuous DC motor			
Reel Drive	1 kw Continuous DC motor incl. offset gearbox			
Differential	Fully accessible			
Cruise Control	Via regenerative braking			
CHASSIS				
Head Assembly	Fixed			
Traction Assembly	Spl't Traction Drum via differential			
Adjustments	Adjustable H.O.C. Via front roller Wrenchless height adjuster by 0.004 inch/0.1mm (nominal)			
REEL AND BLADES				
Diameter	127mm/5"			
Width	22"	26"	30"	34"
Number of Blades	7, 11 or 14			
Cutting Frequency	Electronically adjustable via Smart Phone BLE InfiniApp™			
Height of Cut Range	1.8 - 30mm (0.07" - 1") - model dependent			
Backlapping	Via InfiniApp™			
SPEED				
Mowing	0 - 4 mph			
Transport	0 - 6.4 mph			
Reverse	0.5 - 1 mph			
WEIGHT AND DIMENSIONS				
Length (mm)	1100	1170	1100	1100
Width (mm)	1000	1100	1200	1300
Height (mm)	1210	1210	1210	1160
Weight (Kg) (w/o Grass Basket/battery)	106	114	124	134
WEIGHT AND DIMENSIONS (Packaged for shipping)				
Length (mm)	1210	1210	1210	1210
Width (mm)	1170	1170	1170	1170
Height (mm)	1060	1060	1060	1060
Weight (Kg)	190	220	232	217
ACCESSORY EQUIPMENT				
Reel Groomer (blade & brush)	Contra-Rotating			
Rear Roller Power Brush	Ground Driven - low drag			
TMSystem Compatible	See TMSystem™ Specifications			
Front Roller Options	Smooth, Grooved or Wyle			
Light Kit	LED			
Grain Control	Out Front Brush			
Weight Kit	-		15 - 45kg	
Transport	Trailer Kit Available		TBD	

	FL 22	FL 26	FL 30	FL 34
POWER				
Battery Module Option (battery modules are removable and interchangeable)	30Ah Lithium (20Kg) 60Ah Lithium (40Kg)		30Ah Lithium (20Kg) 60Ah Lithium (40Kg) 105Ah Lithium (43Kg)	
Battery Charger	Delta Q			
Run Time Battery (dependent on set-up and conditions)	2.5 - 3.5 hrs (30Ah) 5 - 7 hrs (60Ah)		2.5 - 3.5 hrs (30Ah) 5 - 7 hrs (60Ah) 8 - 10 hrs (105Ah)	
Approx. recharge time	4 hrs (30Ah) 6 hrs (60Ah)		4 hrs (30Ah) 6 hrs (60Ah) 8 hrs (105Ah)	
TRACTION AND DRIVE				
System Voltage	48V			
Traction Drive	1 kw Continuous DC motor			
Reel Drive	1 kw Continuous DC motor incl. offset gearbox			
Differential	Fully accessible			
Cruise Control	Via regenerative braking			
CHASSIS				
Head Assembly	Floating			
Traction Assembly	Spl't Traction Drum via differential			
Adjustments	Adjustable H.O.C. Via front roller Wrenchless height adjuster by 0.004 inch/0.1mm (nominal)			
REEL AND BLADES				
Diameter	127mm/5"			
Width	22"	26"	30"	34"
Number of Blades	7, 11 or 14			
Cutting Frequency	Electronically adjustable via Smart Phone BLE InfiniApp™			
Height of Cut Range	1.8 - 35mm (0.07" - 1")			
Backlapping	Via InfiniApp™			
SPEED				
Mowing	0 - 4 mph			
Transport	0 - 6.4 mph			
Reverse	0.5 - 1 mph			
WEIGHT AND DIMENSIONS				
Length (mm)	1220	1270	1270	1270
Width (mm)	970	1100	1200	1300
Height (mm)	1200	1210	1210	1130
Weight (Kg)	116	130	141	150
WEIGHT AND DIMENSIONS (Packaged for shipping)				
Length (mm)	1210	1210	1210	1210
Width (mm)	1170	1170	1170	1170
Height (mm)	1060	1060	1060	1060
Weight (Kg)	116	130	141	150
ACCESSORY EQUIPMENT				
Reel Groomer (blade & brush)	Contra-Rotating			
Rear Roller Power Brush	Ground Driven - low drag			
TMSystem Compatible	See TMSystem™ Specifications			
Front Roller Options	Smooth, Grooved or Wyle			
Light Kit	LED			
Grain Control	Out Front Brush			
Weight Kit	-		15 - 45kg	
Transport	Trailer Kit Available		TBD	

	Rotary SM 34
POWER	
Battery Module Option (battery modules are removable and interchangeable)	105Ah Lithium
Battery Charger	Delta Q
Run Time Battery (105Ah)	4 hrs (dependent on set-up and conditions)
Approx. recharge time (60Ah)	8 hrs
TRACTION AND DRIVE	
System Voltage	48V
Traction Drive	1 kw Continuous DC Motor
Deck Drive	2.5 kw Continuous DC Motor
Differential	Fully accessible
Cruise Control	Via regenerative braking
MOWER DECK	
Cutting Width	34"
Deck Shell Construction	Steel
Blades	2.2-in-1 blade 17.9" length
Spindle Construction	4" sealed cast-aluminum housing
Discharge Chute	Bagging
Deck Lift System	Manual
Height Position / Range	15 - 50mm cut w/transport position
BAGGER	
Capacity	70L
Construction	High impact polypropylene chute with nylon bonded monocord mesh grassbag
SPEED	
Mowing	0 - 4 mph
Transport	0 - 6 mph
WEIGHT AND DIMENSIONS	
Length	62"
Width	50"
Height	45"
Weight	190Kg / 480lbs (105Ah)
ACCESSORY EQUIPMENT	
Turf Presenter	Turf Lifter System between Front Roller and Deck
Light Kit	LED Light Kit
Transport	Transport Wheel Kit

INFINICUT
THE PERFECT CUT. EVERY TIME.

Model year 2024